



Black Bear Corporation
 7688 Carnegie Ave, Fontana CA 92336
 Ph: 909-390-0380 Fax: 909-390-0270
 www.blackbearusa.com



Top Running Endtruck- **Double** Girder

September 2012

Capacity	Max. Span (Ft)	HP*2	Total Amp Draw (460v)	Wheel Diam (In.)	Wheel Base (In.)	Overall Length (In.)	Wheel Tread Width (In.)	E.T Weight (lbs/Pair)	Max. Wheel Loading (lbs)
0.5-1 Ton									
TC-05-60-60	29	0.5	1.29	4.7	49.6	59.7	2.2	530	3900
TC-05-60-75	29	0.5	1.29	4.7	49.6	59.7	2.2	530	3900
TC-05-60-85	29	0.5	1.29	4.7	49.6	59.7	2.2	530	3900
TC-05-60-100	29	0.5	1.29	4.7	49.6	59.7	2.2	530	3900
TC-05-80-60	40	0.5	1.29	4.7	69.3	79.4	2.2	615	3900
TC-05-80-75	40	0.5	1.29	4.7	69.3	79.4	2.2	615	3900
TC-05-80-85	40	1	2	4.7	69.3	79.4	2.2	615	3900
TC-05-80-100	40	1	2	4.7	69.3	79.4	2.2	615	3900
TC-05-100-60	52	0.5	1.29	4.7	89.0	99.1	2.2	675	3900
TC-05-100-75	52	1	2	4.7	89.0	99.1	2.2	675	3900
TC-05-100-85	52	1	2	4.7	89.0	99.1	2.2	675	3900
TC-05-100-100	52	1	2	4.7	89.0	99.1	2.2	675	3900
TC-06-120-60	63	1	2	5.9	108.7	118.7	2.6	930	6200
TC-06-120-75	63	1	2	5.9	108.7	118.7	2.6	930	6200
TC-06-120-85	63	1	2	5.9	108.7	118.7	2.6	930	6200
TC-06-120-100	63	1.5	2.58	5.9	108.7	118.7	2.6	930	6200
TC-08-140-60	74	1	2	5.9	126.4	138.6	2.6	1400	6200
TC-08-140-75	74	1	2	5.9	126.4	138.6	2.6	1400	6200
TC-08-140-85	74	1.5	2.59	5.9	126.4	138.6	2.6	1400	6200
TC-08-140-100	74	1.5	2.58	5.9	126.4	138.6	2.6	1400	6200
Capacity	Max. Span (Ft)	HP*2	Total Amp Draw (460v)	Wheel Diam (In.)	Wheel Base (In.)	Overall Length (In.)	Wheel Tread Width (In.)	E.T Weight (lbs/Pair)	Max. Wheel Loading (lbs)
2 Ton									
TC-05-60-60	29	0.5	1.29	4.7	49.6	59.7	2.2	530	3900
TC-05-60-75	29	0.5	1.29	4.7	49.6	59.7	2.2	530	3900
TC-05-60-85	29	1	2	4.7	49.6	59.7	2.2	530	3900
TC-05-60-100	29	1	2	4.7	49.6	59.7	2.2	530	3900
TC-05-80-60	40	0.5	1.29	4.7	69.3	79.4	2.2	615	3900
TC-05-80-75	40	1	2	4.7	69.3	79.4	2.2	615	3900
TC-05-80-85	40	1	2	4.7	69.3	79.4	2.2	615	3900
TC-05-80-100	40	1	2	4.7	69.3	79.4	2.2	615	3900
TC-06-100-60	52	1	2	5.9	89.0	99.1	2.6	845	6200
TC-06-100-75	52	1	2	5.9	89.0	99.1	2.6	845	6200
TC-06-100-85	52	1	2	5.9	89.0	99.1	2.6	845	6200
TC-06-100-100	52	1.5	2.58	5.9	89.0	99.1	2.6	845	6200
TC-08-120-60	62	1	2	7.7	106.7	118.9	2.6	1300	8100
TC-08-120-75	62	1	2	7.7	106.7	118.9	2.6	1300	8100
TC-08-120-85	62	1	2	7.7	106.7	118.9	2.6	1300	8100
TC-08-120-100	62	1.5	2.58	7.7	106.7	118.9	2.6	1300	8100
TC-09-140-60	73	1.5	2.58	8.5	125.6	138.6	2.6	1700	8900



Black Bear Corporation
 7688 Carnegie Ave, Fontana CA 92336
 Ph: 909-390-0380 Fax: 909-390-0270
www.blackbearusa.com



Top Running Endtruck- **Double** Girder

Capacity	Max. Span (Ft)	HP*2	Total Amp Draw (460v)	Wheel Diam (In.)	Wheel Base (In.)	Overall Length (In.)	Wheel Tread Width (In.)	E.T Weight (lbs/Pair)	Max. Wheel Loading (lbs)
2 Ton									
TC-09-140-75	73	1.5	2.58	8.5	125.6	138.6	2.6	1700	8900
TC-09-140-85	73	1.5	2.58	8.5	125.6	138.6	2.6	1700	8900
TC-09-140-100	73	2	3.44	8.5	125.6	138.6	2.6	1700	8900
Capacity	Max. Span (Ft)	HP*2	Total Amp Draw (460v)	Wheel Diam (In.)	Wheel Base (In.)	Overall Length (In.)	Wheel Tread Width (In.)	E.T Weight (lbs/Pair)	Max. Wheel Loading (lbs)
3 Ton									
TC-06-100-60	52	1	2	5.9	89.0	99.1	2.6	845	6200
TC-06-100-75	52	1	2	5.9	89.0	99.1	2.6	845	6200
TC-06-100-85	52	1	2	5.9	89.0	99.1	2.6	845	6200
TC-06-100-100	52	1.5	2.58	5.9	89.0	99.1	2.6	845	6200
TC-08-100-60	51	1	2	7.7	87.0	99.2	2.6	1205	8100
TC-08-100-75	51	1	2	7.7	87.0	99.2	2.6	1205	8100
TC-08-100-85	51	1.5	2.58	7.7	87.0	99.2	2.6	1205	8100
TC-08-100-100	51	1.5	2.58	7.7	87.0	99.2	2.6	1205	8100
TC-09-120-60	62	1	2	8.5	105.9	118.9	2.6	1585	8900
TC-09-120-75	62	1.5	2.58	8.5	105.9	118.9	2.6	1585	8900
TC-09-120-85	62	1.5	2.58	8.5	105.9	118.9	2.6	1585	8900
TC-09-120-100	62	1.5	2.58	8.5	105.9	118.9	2.6	1585	8900
TC-10-140-60	72	1.5	2.58	8.5	122.8	138.6	2.6	1700	8900
TC-10-140-75	72	1.5	2.58	8.5	122.8	138.6	2.6	1700	8900
TC-10-140-85	72	2	3.44	8.5	122.8	138.6	2.6	1700	8900
TC-10-140-100	72	2	3.44	8.5	122.8	138.6	2.6	1700	8900
Capacity	Max. Span (Ft)	HP*2	Total Amp Draw (460v)	Wheel Diam (In.)	Wheel Base (In.)	Overall Length (In.)	Wheel Tread Width (In.)	E.T Weight (lbs/Pair)	Max. Wheel Loading (lbs)
5 Ton									
TC-08-100-60	51	1	2	7.7	87.0	99.2	2.6	1205	8100
TC-08-100-75	51	1	2	7.7	87.0	99.2	2.6	1205	8100
TC-08-100-85	51	1	2	7.7	87.0	99.2	2.6	1205	8100
TC-08-100-100	51	1.5	2.58	8.5	87.0	99.2	2.6	1205	8900
TC-09-100-60	50	1	2	8.5	86.2	99.2	2.6	1385	8900
TC-09-100-75	50	1	2	8.5	86.2	99.2	2.6	1385	8900
TC-09-100-85	50	1	2	8.5	86.2	99.2	2.6	1385	8900
TC-09-100-100	50	2	3.44	8.5	86.2	99.2	2.6	1385	8900
TC-09-120-60	62	1.5	2.58	8.5	105.9	118.9	2.6	1585	8900
TC-09-120-75	62	1	2	8.5	105.9	118.9	2.6	1585	8900
TC-09-120-85	62	1	2	8.5	105.9	118.9	2.6	1585	8900
TC-09-120-100	62	2	3.44	8.5	105.9	118.9	2.6	1585	8900
TC-10-140-60	72	1.5	2.58	9.8	122.8	138.7	2.8	2130	19400
TC-10-140-75	72	1.5	2.58	9.8	122.8	138.7	2.8	2130	19400
TC-10-140-85	72	2	3.44	9.8	122.8	138.7	2.8	2130	19400
TC-10-140-100	72	2	3.44	9.8	122.8	138.7	2.8	2130	19400



Black Bear Corporation
 7688 Carnegie Ave, Fontana CA 92336
 Ph: 909-390-0380 Fax: 909-390-0270
 www.blackbearusa.com



Top Running Endtruck- **Double** Girder

Capacity	Max. Span (Ft)	HP*2	Total Amp Draw (460v)	Wheel Diam (In.)	Wheel Base (In.)	Overall Length (In.)	Wheel Tread Width (In.)	E.T Weight (lbs/Pair)	Max. Wheel Loading (lbs)
7.5 Ton									
TC-10-120-60	60	1.5	2.58	9.8	103.2	119.1	2.8	1965	19400
TC-10-120-75	60	1.5	2.58	9.8	103.2	119.1	2.8	1965	19400
TC-10-120-85	60	2	3.44	9.8	103.2	119.1	2.8	1965	19400
TC-10-120-100	60	2	3.44	9.8	103.2	119.1	2.8	1965	19400
TC-10-140-60	72	1.5	2.58	9.8	122.8	138.7	2.8	2130	19400
TC-10-140-75	72	2	3.44	9.8	122.8	138.7	2.8	2130	19400
TC-10-140-85	72	2	3.44	9.8	122.8	138.7	2.8	2130	19400
TC-10-140-100	72	3	4.59	9.8	122.8	138.7	2.8	2130	19400
TC-12-160-60	82	3	3.44	11.8	140.2	158.4	3.4	2670	22000
TC-12-160-75	82	2	3.44	11.8	140.2	158.4	3.4	2670	22000
TC-12-160-85	82	3	4.59	11.8	140.2	158.4	3.4	2670	22000
TC-12-160-100	82	3	4.59	11.8	140.2	158.4	3.4	2670	22000
Capacity	Max. Span (Ft)	HP*2	Total Amp Draw (460v)	Wheel Diam (In.)	Wheel Base (In.)	Overall Length (In.)	Wheel Tread Width (In.)	E.T Weight (lbs/Pair)	Max. Wheel Loading (lbs)
10 Ton									
TC-10-140-60	72	1	2	9.8	122.8	138.7	2.8	2130	19400
TC-10-140-75	72	1	2	9.8	122.8	138.7	2.8	2130	19400
TC-10-140-85	72	2	3.44	9.8	122.8	138.7	2.8	2130	19400
TC-10-140-100	72	2	3.44	9.8	122.8	138.7	2.8	2130	19400
TC-12-140-60	70	3	3.44	11.8	120.5	138.7	3.4	2430	22000
TC-12-140-75	70	3	4.59	11.8	120.5	138.7	3.4	2430	22000
TC-12-140-85	70	4	4.59	11.8	120.5	138.7	3.4	2430	22000
TC-12-140-100	70	4	5.72	11.8	120.5	138.7	3.4	2430	22000
TC-12-160-60	82	2	3.44	11.8	140.2	158.4	3.4	2670	22000
TC-12-160-75	82	3	4.59	11.8	140.2	158.4	3.4	2670	22000
TC-12-160-85	82	3	4.59	11.8	140.2	158.4	3.4	2670	22000
TC-12-160-100	82	4	5.72	11.8	140.2	158.4	3.4	2670	22000
Capacity	Max. Span (Ft)	HP*2	Total Amp Draw (460v)	Wheel Diam (In.)	Wheel Base (In.)	Overall Length (In.)	Wheel Tread Width (In.)	E.T Weight (lbs/Pair)	Max. Wheel Loading (lbs)
15 Ton									
TC-12-140-60	70	3	3.44	11.8	120.5	138.7	3.4	2430	22000
TC-12-140-75	70	3	3.44	11.8	120.5	138.7	3.4	2430	22000
TC-12-140-85	70	4	4.59	11.8	120.5	138.7	3.4	2430	22000
TC-12-140-100	70	4	4.59	11.8	120.5	138.7	3.4	2430	22000
TC-12-160-60	82	2	3.44	11.8	140.2	158.4	3.4	2670	22000
TC-12-160-75	82	3	4.59	11.8	140.2	158.4	3.4	2670	22000
TC-12-160-85	82	3	4.59	11.8	140.2	158.4	3.4	2670	22000
TC-12-160-100	82	3	4.59	11.8	140.2	158.4	3.4	2670	22000
TC-16-160-60	80	3	3.44	15.8	137.8	158.4	3.4	3880	28500
TC-16-160-75	80	3	4.59	15.8	137.8	158.4	3.4	3880	28500
TC-16-160-85	80	3	4.59	15.8	137.8	158.4	3.4	3880	28500
TC-16-160-100	80	4	5.72	15.8	137.8	158.4	3.4	3880	28500



Black Bear Corporation
 7688 Carnegie Ave, Fontana CA 92336
 Ph: 909-390-0380 Fax: 909-390-0270
 www.blackbearusa.com



Top Running Endtruck- **Single Girder**

September 2012

Capacity 0.5-1 Ton	Max SPAN (FT)	HP*2	Total Amp Draw (460V)	Wheel Diam (In)	WHEEL BASE (In.)	Overall Length (In.)	Wheel Tread Width (in)	Est. WT (lbs)	Max Wheel Loading (Pair)
TC-05-60-60	33	0.5	1.29	4.7	49.6	59.7	2.2	530	3900
TC-05-60-75	33	0.5	1.29	4.7	49.6	59.7	2.2	530	3900
TC-05-60-85	33	0.5	1.29	4.7	49.6	59.7	2.2	530	3900
TC-05-60-100	33	0.5	1.29	4.7	49.6	59.7	2.2	530	3900
TC-05-80-60	46	0.5	1.29	4.7	69.3	79.4	2.2	615	3900
TC-05-80-75	46	0.5	1.29	4.7	69.3	79.4	2.2	615	3900
TC-05-80-85	46	0.5	1.29	4.7	69.3	79.4	2.2	615	3900
TC-05-80-100	46	0.5	1.29	4.7	69.3	79.4	2.2	615	3900
TC-06-100-60	59	0.5	1.29	5.9	89	99.1	2.6	845	6200
TC-06-100-75	59	0.5	1.29	5.9	89	99.1	2.6	845	6200
TC-06-100-85	59	0.5	1.29	5.9	89	99.1	2.6	845	6200
TC-06-100-100	59	1	2	5.9	89	99.1	2.6	845	6200
TC-08-120-60	71	0.5	1.29	7.7	106.7	118.9	2.6	1300	8100
TC-08-120-75	71	0.5	1.29	7.7	106.7	118.9	2.6	1300	8100
TC-08-120-85	71	0.5	1.29	7.7	106.7	118.9	2.6	1300	8100
TC-08-120-100	71	1	2	7.7	106.7	118.9	2.6	1300	8100
Capacity 2 Ton	Max SPAN (FT)	HP*2	Total Amp Draw (460V)	Wheel Diam (In)	WHEEL BASE (In.)	Overall Length (In.)	Wheel Tread Width (in)	Est. WT (lbs)	Max Wheel Loading (Pair)
TC-06-60-60	33	0.5	1.29	5.9	49.6	59.7	2.6	671	6200
TC-06-60-75	33	0.5	1.29	5.9	49.6	59.7	2.6	671	6200
TC-06-60-85	33	0.5	1.29	5.9	49.6	59.7	2.6	671	6200
TC-06-60-100	33	1	2	5.9	49.6	59.7	2.6	671	6200
TC-06-80-60	46	0.5	1.29	5.9	69.3	79.4	2.6	765	6200
TC-06-80-75	46	0.5	1.29	5.9	69.3	79.4	2.6	765	6200
TC-06-80-85	46	1	2	5.9	69.3	79.4	2.6	765	6200
TC-06-80-100	46	1	2	5.9	69.3	79.4	2.6	765	6200
TC-08-100-60	58	0.5	1.29	7.7	87	99.2	2.6	1205	8100
TC-08-100-75	58	0.5	1.29	7.7	87	99.2	2.6	1205	8100
TC-08-100-85	58	1.5	2	7.7	87	99.2	2.6	1205	8100
TC-08-100-100	58	1	2	7.7	87	99.2	2.6	1205	8100
TC-09-120-60	71	0.5	1.29	8.5	105.9	118.9	2.6	1585	8900
TC-09-120-75	71	1	2	8.5	105.9	118.9	2.6	1585	8900
TC-09-120-85	71	1	2	8.5	105.9	118.9	2.6	1585	8900
TC-09-120-100	71	1	2	8.5	105.9	118.9	2.6	1585	8900



Black Bear Corporation
 7688 Carnegie Ave, Fontana CA 92336
 Ph: 909-390-0380 Fax: 909-390-0270
 www.blackbearusa.com



Top Running Endtruck- **Single** Girder

Capacity 3 Ton	Max SPAN (FT)	HP*2	Total Amp Draw (460V)	Wheel Diam (In)	WHEEL BASE (In.)	Overall Length (In.)	Wheel Tread Width (in)	Est. WT (lbs)	Max Wheel Loading (Pair)
TC-06-60-60	33	0.5	1.29	5.9	49.6	59.7	2.6	671	6200
TC-06-60-75	33	0.5	1.29	5.9	49.6	59.7	2.6	671	6200
TC-06-60-85	33	1	2	5.9	49.6	59.7	2.6	671	6200
TC-06-60-100	33	1	2	5.9	49.6	59.7	2.6	671	6200
TC-08-80-60	45	0.5	1.29	7.7	67.3	79.5	2.6	960	8100
TC-08-80-75	45	0.5	1.29	7.7	67.3	79.5	2.6	960	8100
TC-08-80-85	45	1	2	7.7	67.3	79.5	2.6	960	8100
TC-08-80-100	45	1	2	7.7	67.3	79.5	2.6	960	8100
TC-08-100-60	58	0.5	1.29	7.7	87	99.2	2.6	1205	8100
TC-08-100-75	58	1	2	7.7	87	99.2	2.6	1205	8100
TC-08-100-85	58	1.5	2	7.7	87	99.2	2.6	1205	8100
TC-08-100-100	58	1	2	7.7	87	99.2	2.6	1205	8100
TC-09-120-60	71	1	2	8.5	105.9	118.9	2.6	1585	8900
TC-09-120-75	71	1	2	8.5	105.9	118.9	2.6	1585	8900
TC-09-120-85	71	1	2	8.5	105.9	118.9	2.6	1585	8900
TC-09-120-100	71	1.5	2.58	8.5	105.9	118.9	2.6	1585	8900
Capacity 5 Ton	Max SPAN (FT)	HP*2	Total Amp Draw (460V)	Wheel Diam (In)	WHEEL BASE (In.)	Overall Length (In.)	Wheel Tread Width (in)	Est. WT (lbs)	Max Wheel Loading (Pair)
TC-09-80-60	44	1	2	8.5	66.5	79.5	2.6	1270	8900
TC-09-80-75	44	1	2	8.5	66.5	79.5	2.6	1270	8900
TC-09-80-85	44	1	2	8.5	66.5	79.5	2.6	1270	8900
TC-09-80-100	44	1	2	8.5	66.5	79.5	2.6	1270	8900
TC-10-100-60	56	1	2	9.8	83.5	99.4	2.8	1815	19400
TC-10-100-75	56	1	2	9.8	83.5	99.4	2.8	1815	19400
TC-10-100-85	56	1	2	9.8	83.5	99.4	2.8	1815	19400
TC-10-100-100	56	1.5	2.58	9.8	83.5	99.4	2.8	1815	19400
TC-10-120-60	69	1	2	9.8	103.2	119.1	2.8	1965	19400
TC-10-120-75	69	1	2	9.8	103.2	119.1	2.8	1965	19400
TC-10-120-85	69	1.5	2.58	9.8	103.2	119.1	2.8	1965	19400
TC-10-120-100	69	1.5	2.58	9.8	103.2	119.1	2.8	1965	19400



Black Bear Corporation
 7688 Carnegie Ave, Fontana CA 92336
 Ph: 909-390-0380 Fax: 909-390-0270
 www.blackbearusa.com



Top Running Endtruck- **Single** Girder

Capacity 7.5 Ton	Max SPAN (FT)	HP*2	Total Amp Draw (460V)	Wheel Diam (In)	WHEEL BASE (In.)	Overall Length (In.)	Wheel Tread Width (in)	Est. WT (lbs)	Max Wheel Loading (Pair)
TC-10-80-60	43	1	2	9.8	63.8	79.7	2.8	1660	19400
TC-10-80-75	43	1	2	9.8	63.8	79.7	2.8	1660	19400
TC-10-80-85	43	1.5	2.58	9.8	63.8	79.7	2.8	1660	19400
TC-10-80-100	43	1.5	2.58	9.8	63.8	79.7	2.8	1660	19400
TC-12-100-60	54	1	2	11.8	81.1	99.4	3.4	2080	22000
TC-12-100-75	54	1.5	2.58	11.8	81.1	99.4	3.4	2080	22000
TC-12-100-85	54	1.5	2.58	11.8	81.1	99.4	3.4	2080	22000
TC-12-100-100	54	2	3.44	11.8	81.1	99.4	3.4	2080	22000
Capacity 10 Ton	Max SPAN (FT)	HP*2	Total Amp Draw (460V)	Wheel Diam (In)	WHEEL BASE (In.)	Overall Length (In.)	Wheel Tread Width (in)	Est. WT (lbs)	Max Wheel Loading (Pair)
TC-10-80-60	43	1	2	9.8	63.8	79.7	2.8	1660	19400
TC-10-80-75	43	1.5	2.58	9.8	63.8	79.7	2.8	1660	19400
TC-10-80-85	43	1.5	2.58	9.8	63.8	79.7	2.8	1660	19400
TC-10-80-100	43	2	3.44	9.8	63.8	79.7	2.8	1660	19400
TC-12-100-60	54	1.5	2.58	11.8	81.1	99.4	3.4	2080	22000
TC-12-100-75	54	1.5	2.58	11.8	81.1	99.4	3.4	2080	22000
TC-12-100-85	54	1.5	2.58	11.8	81.1	99.4	3.4	2080	22000
TC-12-100-100	54	2	3.44	11.8	81.1	99.4	3.4	2080	22000